



HYDRAULIC DOUBLE-SCISSOR LIFT

JUMBO LIFT

FLEXIBILITY & TECHNOLOGY

WITH PATENTED
HyperFlow[®]
technology

WITH
TECHNOLOGY



THE MULTI-TASK EXPERT

- ✓ Very low construction height for above or in-ground installation
- ✓ Adjustable length of the lifting platforms
- ✓ NT and patented HyperFlow[®] Technologies: 100% hydraulic, 100% safe

3500 KG | 4000 KG

Made
in
Germany



HYDRAULIC DOUBLE-SCISSOR LIFT

JUMBO LIFT

Fast, flexible and always ready

A flexible double-scissor lift, suitable for a large range of works and vehicles, from small cars to SUVs and sports cars.

Long-lasting and safe, it features the best technology on the market: the patented hydraulic system HyperFlow®.

A multi-tasking expert

- ✓ Suitable for a large range of vehicles up to short wheelbase vans
- ✓ Flexible lifting platform: Access ramps can be locked and unlocked to adapt the platform length to long and short vehicles
- ✓ Flat construction: Suitable for very low clearance vehicles
- ✓ X-Tend: 2x variable in length: lockable ramps and extendable platform extensions



Flexible width

In addition to the foldable extensions and its flexible installation width, the JUMBO LIFT HF X-Tend comes with extendable platforms.

6 reasons why the JUMBO is low maintenance

With its **compact oil-submerged motor** and **high quality steel construction**, the JUMBO is built to be long-lasting and low maintenance.

The JUMBO **does not need any mechanical lock** thanks to the **redundant hydraulic system** and **automatic synchronization**.

Almost wear free with **just few electrical and no pneumatic components and no mechanical lock**.

All connections are fitted with lubricating points, ensuring smooth operation over time.



TOP FEATURES AT ONE GLANCE

- **Adapts to a wide range of vehicles**
Flat construction and adjustable lifting platform
- **Lifting height**
Effective lifting height of 2000 mm
- **HyperFlow® technology**
Low maintenance and perfect synchronization over time
- **Flexible**
Flexible installation width, no air supply needed, easy to relocate

JUMBO LIFT 3500, 4000: WE OFFER THE RIGHT CAPACITY FOR ANY WORKSHOP



Very flat construction: Ideal for very low clearance vehicles

New maximum length of 2320 mm with extendable platforms. (Version X-Tend)

Recessed installation for low clearance vehicles, ideally with the optional galvanized recess frame

The Nussbaum-Commander offers variable lowering speeds. (Version X-Tend)



CHOOSE YOUR JUMBO SIZE

JUMBO LIFT	3500	4000	
Lifting capacity (kg)	3500	4000	
Lifting time approx. (sec)	35	35	
Lifting height (mm)	2000	2000	
Drive-on height (mm)	105	135	
Installation depth (mm)	105	135	
Recommended total width (mm)	2020-2120	2020-2120	
Platform width (mm)	610	610	
Platform length (mm)	Version NT Short Version NT Version HF X-Tend	1460-2060 1460-2160 1550-2320	- 1460-2160 1550-2320
Power supply (V/Hz)	400/50	400/50	
Motor (kW)	3	3	


ACCESSORIES



Truncated pyramid pad



Polymer pads
50x150x340 mm



Polymer pads
100x150x340 mm

More accessories available

ACCESSORIES	3500	4000
Rubber truncated pyramid pad	✓	✓
Polymer pad 50x150x340 mm	✓	✓
Polymer pad 100x150x340 mm	✓	✓
Tuning ramps for low clearance vehicles / set = 4 units	✓	✓

OPTIONAL SURFACE TREATMENT	3500	4000
Fire galvanized	✓	✓